## INSTALLATION INSTRUCTIONS

FOR ITEM 21465 American Craftsman Flushmount



CAUTION: FAILURE TO INSTALL THIS FIXTURE PROPERLY MAY RESULT IN SERIOUS PERSONAL INJURY OR DEATH AND PROPERTY DAMAGE. We recommend installation by a licensed electrician.

This product must be installed in accordance with applicable installation code(s), by a person familiar with the construction and operation of the product and the hazards involved.\*

**Caution**: Do not exceed maximum wattage noted on fixture. Use only recommended bulbs with fixture.

## Caution:

## Be sure power is off at the main breaker box prior to installation. Read all instructions in their entirety before beginning installation.

- 1. Carefully unpack all components and make certain that everything is accounted for.
- 2. Remove Brass Ball and Cap from bottom of Shade to separate from Shade from Canopy. Reserve Brass Ball and Cap.
- 3. Remove Brass Balls from Canopy to release Crossbar with Studs. Reserve Brass Balls.
- 4. Using Customer Supplied Hardware, affix Crossbar to Junction Box ensuring that connection is suitable to hold a minimum of 20lbs and that Electrical Supply Wires remain accessible.
- 5. Following All Local Codes and Procedures, make connection from Fixture Lead Wires to Supply Wires.
- 6. Lift Canopy up to ceiling allowing Crossbar Studs to pass through. Secure Canopy with reserved Brass Balls.
- 7. Install 2-E26 60Watt Bulbs(not included) into Sockets.
- 8. Lift Shade up to ceiling allowing Threaded Rod to pass through. Replace Brass Cap and Secure with reserved Brass Ball.
- 9. Power on and ENJOY!!!

